

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade Page: 1/8
Revision Date: 2012-08-21 Print date: 2012-08-21
Product No.: SDS-ID: GB-EN/2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: Prolan Light, Medium and Heavy Grade
Container size: 1l, 2,5l, 5l, 10l, 20l, 25l

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Lubricant.
Corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet

Supplier: Denrex ApS
Daniavej 33, Assens
DK- 9550 Mariager
Tel: +45 24428188
Fax: +45 98548188
In@denrex.com
www.denrex.com
Responsible for safety data sheet authoring: SDS_info@dhigroup.com

1.4. Emergency telephone number

Emergency telephone: 112

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is not classified.

Human health: Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. The harmful effects may increase in used oil.

Environment: Oil spills are generally hazardous to the environment. The product contains volatile, organic compounds which have a photochemical ozone creation potential.

2.2. Label elements

Based on information from the manufacturer regarding the chemical composition, the product is not liable to classification, but the following labelling must be applied:

Safety data sheet available for professional user on request.

2.3. Other hazards

PBT/vPvB: Not relevant.

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade Page: 2/8
Revision Date: 2012-08-21 Print date: 2012-08-21
Product No.: SDS-ID: GB-EN/2.0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: Lanolin and organic solvent.

67/548/EEC:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
>50	64742-48-9	265-150-3	-	Naphtha (petroleum), hydrotreated heavy	Xn;R65 R66	P

GHS/CLP:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
>50	64742-48-9	265-150-3	-	Naphtha (petroleum), hydrotreated heavy	Asp. Tox. 1;H304 EUH066	P

References: The full text for all R-phrases and hazard statements are displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions.

Skin contact: Remove contaminated clothing.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Not known.

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade Page: 3/8
Revision Date: 2012-08-21 Print date: 2012-08-21
Product No.: SDS-ID: GB-EN/2.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards: During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-fighters: Wear a self contained breathing apparatus in fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid inhalation of vapours and contact with skin and eyes. Follow precautions for safe handling described in this safety data sheet.

6.2. Environmental precautions

Environmental precautions: Avoid discharge into water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Clean contaminated area with oil-removing material. In case of spills, beware of slippery floors and surfaces.

6.4. Reference to other sections

References: For personal protection, see section 8.
For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Avoid inhalation of vapours/spray and contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets. Observe good chemical hygiene practices.

Technical measures: Keep the workplace clean. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

Technical precautions: When working with heated oil, mechanical ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow rules for flammable liquids.

Storage conditions: Store in tightly closed original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific use(s): Not relevant.

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade Page: 4/8
Revision Date: 2012-08-21 Print date: 2012-08-21
Product No.: SDS-ID: GB-EN/2.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
-	Normal and branched chain alkanes \geq C7 (excluding n-Heptane)	-	1200 mg/m ³	TWA	-	EH40

8.2. Exposure controls

<u>Engineering measures:</u>	Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours and spray mist. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.
<u>Personal protection:</u>	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
<u>Respiratory equipment:</u>	Use respiratory equipment with gas filter, type A2. When spraying: Use respiratory equipment with combination filter, type A2/P3.
<u>Hand protection:</u>	Risk of contact: Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.
<u>Eye protection:</u>	Risk of contact: Wear goggles/face shield.
<u>Skin protection:</u>	Wear apron or protective clothing in case of contact.
<u>Hygiene measures:</u>	Wash hands after handling.
<u>Environmental Exposure Controls:</u>	Not available.

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade
Revision Date: 2012-08-21
Product No.:

Page: 5/8
Print date: 2012-08-21
SDS-ID: GB-EN/2.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance: Liquid. Light brown.
Odour: characteristic of solvents
pH: not relevant
Melting point: not available
Boiling point: 110-200°C
Flash point: 66°C
Evaporation rate: Evaporation rate (BuAc=100): 5
Explosion limits: 1-6 vol%
Vapour pressure: 0,4 kPa (38°C)
Vapour density: 5,3
Relative density: 0,81-0,83 (24°C)
Solubility: Insoluble in water.
Auto-ignition temperature (°C): 227°C
Viscosity: not available

9.2. Other information

Other data: Volatile by vol. (%)80

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: None known.

10.2. Chemical stability

Stability: Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions: None known.

10.4. Conditions to avoid

Conditions/materials to avoid: Heating.

10.5. Incompatible materials

Incompatible materials: Strong acids. Strong oxidising substances.

10.6. Hazardous decomposition products

Hazardous decomposition products: None in particular.

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade Page: 6/8
Revision Date: 2012-08-21 Print date: 2012-08-21
Product No.: SDS-ID: GB-EN/2.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation: Vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact: Prolonged contact may cause redness, irritation and dry skin.

Eye contact: May irritate and cause redness and pain.

Ingestion: May irritate and cause malaise. May be absorbed in the body and cause dizziness, nausea and vomiting.

Specific effects: Frequent inhalation of even small concentrations may cause irritability, fatigue and memory failure and eventually permanent damage to the nervous system, including the brain.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: There are no data on the ecotoxicity of this product. Oil spills are generally hazardous to the environment.

12.2. Persistence and degradability

Degradability: The degradability of the product has not been stated.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: Not relevant.

12.6. Other adverse effects

Other adverse effects: The product contains volatile, organic compounds which have a photochemical ozone creation potential.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 20 01 13

SAFETY DATA SHEET

Product name: Prolan Light, Medium and Heavy Grade Page: 7/8
Revision Date: 2012-08-21 Print date: 2012-08-21
Product No.: SDS-ID: GB-EN/2.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN-No: -

14.2. UN proper shipping name

Proper Shipping Name: -

14.3. Transport hazard class(es)

Class: -

14.4. Packing group

PG: -

14.5. Environmental hazards

Marine pollutant: -

Environmentally Hazardous substance: -

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.
The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).
EH40/2005, Workplace exposure limits 2005, with amendments.
The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

15.2. Chemical Safety Assessment

CSA status: Not relevant.

SAFETY DATA SHEET

Product name:	Prolan Light, Medium and Heavy Grade	Page:	8/8
Revision Date:	2012-08-21	Print date:	2012-08-21
Product No.:		SDS-ID:	GB-EN/2.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 1-16

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

Wording of

R-phrases/H-statements:

R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.
www.dhigroup.com.
